VULCAN® GAS & ELECTRIC HOT WATER





(*) ELECTRIC



THAT'S VULCAN® VALUE

High quality and performance at a very affordable price. Three good reasons why Vulcan is such a popular choice for reliable water heating.

Vulcan is built with the best: Quality materials and proven technology make Vulcan a great choice.

Vulcan is tough: The Vulcan storage cylinder is made from high strength steel tough enough to withstand varying water and heating cycle pressures.

Vulcan is adaptable: The balanced flue and steel jackets make Vulcan gas models easy to install and easy to live with. They can be installed on an approved base against a wall or recessed into a wall cavity.

Vulcan has backup: If you need a spare part for your Vulcan it's good to know they are readily available across the country and can be serviced by most plumbers or electricians.




Many households change over time, so it's important to make sure you select the model to suit your needs both now and as your family grows. Take into consideration appliances such as washing machines and dishwashers, which can use as much hot water as one person. Also allow for family additions and don't forget - small children grow into large teenagers.


Use the charts below as a guide for calculating your average usage, and for selecting the right Vulcan model for you.

Vulcan Gas						
			Model			
Vulcan Quick Recovery	5 Years†		648135	648170		
Trim Kit	-		FK135	FK170		
AGA Energy Gas Rating	Stars		4	4		
Storage Capacity	Litres		135	170		
Dimensions	А	mm	1558	1858		
	В	mm	422	422		
	С	mm	502	502		
	D	mm	988	1213		
	Е	mm	328	403		
	F	mm	298	298		
	G	mm	1478	1778		
	K	mm	473	473		
	L	mm	208	208		
Approx. Weight Empty	kg		59	69		
Relief Valve Setting	kPa		1400	1400		
ECV Setting #	kPa		1200	1200		
Max. Supply Pressure	kPa					
With Expansion Control		960	960			
Without Expansion Cont		1120	1120			
Hourly Gas Consumption						
	Natural	MJ	27	27		
	Propane	MJ	27	n/a		
Water Connections (LHS)			Rp ¾	Rp 3/4		
Gas Connection			Rp ⅓	Rp ½		

Note: Outdoor models must be installed with the back of the water heater against a wall. Minimum distances from the flue terminal to openings into a building, corners and return walls apply.

Storage Tank Dimensions





Vulcan Electric									
	Warranty								
Vulcan Single Element	5 Years†			601080	601125	661160			
Left Handed	10 Years†*						661250	661315	661400
Vulcan Single Element Dual Hand	5 Years†		691050						
Vulcan Twin Element	10 Years†*							662315	662400
Hot Water Delivery	Litres		50	80	125	160	250	315	400
Storage Capacity	Litres		53	90	135	165	270	325	410
Boost Capacity	Litres		-	-	-	-	-	50	90
Dimensions	А	mm	695	875	1242	1610	1395	1640	1840
	В	mm	400	460	480	480	640	640	690
	С	mm	429	492	515	515	675	675	730
	D	mm	397	475	852	1332	1117	1317	1479
	Е	mm	142	194	195	104	73	113	121
	F	mm	80	112	112	84	128	128	129
	G	mm	-	-	-	-	-	1255	1346
	Н	degrees	26	22	22	23	32	32	30
	J	degrees	59	60	60	58	88	88	83
Approx. Weight Empty	kg		26	32	44	52	70	88	112
Inlet/Outlet Connections	RP		Rp 3/4						
Relief Valve Setting	kPa		1000	1000	1000	1400	1000	1000	1000
ECV Setting #	kPa		850	850	850	1200	850	850	850
Max. Supply Pressure	kPa								
With Expansion Control Valve		680	680	680	960	680	680	680	
Without Expansion Control Valve		800	800	800	1120	800	800	800	

Note: All water heaters operate on 240 volt single phase electricity supply.

ECV not supplied with water heater.

- † Warranty: 10 years on cylinder, 1 year on parts and labour (Electric 661250, 661315 & 661400). 5 years on cylinder, 3 years labour on cylinder, 1 year on parts and labour (Electric 691050, 601080, 601125,661160, Gas 648135, 648170).
- * 10 year cylinder warranty applies to products manufactured on or after 20.11.2017 Conditions apply. See the Vulcan warranty set out in the Owner's Guide & Installation Instructions or view at www.vulcan.com.au/warranty.

SIZING GUIDE								
Vulcan Gas								
Storage Capacity in Litres		135	170					
No. of people - Moderate Climate		2-4	3-5					
No. of people – Cool Climate		2-3	3-4					
Vulcan Electric								
Delivery in Litres	50	80	125	160	250	315	400	
Continuous Tariff								
No. of People	1-2	1-2	2-3	2-4	3-5	4-6	5-9	
No. of Bedrooms					1-2	3	4-5	
Off-Peak Tariff								
No. of People					1-3	2-4	4-6	

Materials and specifications are subject to change without notice.

Rheem Australia Pty Ltd.

PO Box 7508 Silverwater NSW 2128, Australia

National Sales Phone: 132 552 National Sales Fax: 1300 554 821 National Service Phone: 131 031

- Registered trademark of Rheem Australia Pty Ltd.







